

RTS Application Guide

FORD

This fitment guide applies to vehicles with O.E. suspension/wheel wells/and brakes unless otherwise noted.

Other sizes and offsets are available/please call the Sales and Tech Department for more information

Mustang 2015+ GT with Brembo

15" Front Rotors, 5x4.5 [A] bolt circle

14mmx1.5 Stud and lug nuts. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
18"	High	18x5.0	Front	-23	2.10	71HB8050A21A	71HP8050A21A	75HB8050A21A	76HB8050A21A	77HB8050A21A
	Low	18x9.5	Rear only	50	7.20	71LB8095A72A	71LP8095A72A	75LB8095A72A	76LB8095A72A	77LB8095A72A
	Low	18x10.0	Rear only	56	7.70	71LB8100A77A	71LP8100A77A	75LB8100A77A	76LB8100A77A	77LB8100A77A

20"	High	20x7.0	Front	6	4.25	71HB0070A43A	71HP0070A43A	75HB0070A43A	76HB0070A43A	77HB0070A43A
	High	20x8.0	Front	19	5.25	71HB0080A53A	71HP0080A53A	75HB0080A53A	76HB0080A53A	77HB0080A53A
	High	20x9.0	Front	32	6.25	71HB0090A63A	71HP0090A63A	75HB0090A63A	76HB0090A63A	77HB0090A63A
	Low	20x10.5	Rear only	43	7.5	71LB0105A75A	71LP0105A75A	75LB0105A75A	76LB0105A75A	77LB0105A75A
	Low	20x11.0	Rear only	50	8	71LB0110A80A	71LP0110A80A	75LB0110A80A	76LB0110A80A	77LB0110A80A

Mustang 2015+ base and GT with std 14" rotors.

5x4.5 [A] bolt circle

14mmx1.5 Stud and lug nuts. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Medium	15x9	Rear only	37	6.5	71MB-509A65A^	71MP-509A65A^	75MB-509A65A^	76MB-509A65A^	77MB-509A65A^
	Medium	15x10	Rear only	50	7.5	71MB-510A75A^	71MP-510A75A^	75MB-510A75A^	76MB-510A75A^	77MB-510A75A^

^ Denotes: Requires Rear brake conversion and Rear Sway bar Relocation Brackets required

17"	High	17x5.0	Front	-21	2.2	71HB7050A22A	71HP7050A22A	75HB7050A22A	76HB7050A22A	77HB7050A22A
	High	17x8.0	Front	18	5.2	71HB7080A52A	71HP7080A52A	75HB7080A52A	76HB7080A52A	77HB7080A52A
	High	17x9.0	Front	31	6.2	71HB7090A62A	71HP7090A62A	75HB7090A62A	76HB7090A62A	77HB7090A62A
	High	17x9.5	Front	37	6.7	71HB7095A67A	71HP7095A67A	75HB7095A67A	76HB7095A67A	77HB7095A67A
	Low	17x9.5	Rear only	32	6.5	71LB7095A65A	71LP7095A65A	75LB7095A65A	76LB7095A65A	77LB7095A65A
	Low	17x10.0	Rear only	64	8	71LB7100A80A	71LP7100A80A	75LB7100A80A	76LB7100A80A	77LB7100A80A
	Low	17x10.5	Rear only	57	8	71LB7105A80A	71LP7105A80A	75LB7105A80A	76LB7105A80A	77LB7105A80A

18"	High	18x5.0	Front	-23	2.1	71HB8050A21A	71HP8050A21A	75HB8050A21A	76HB8050A21A	77HB8050A21A
	High	18x8.0	Front	15	5.1	71HB8080A51A	71HP8080A51A	75HB8080A51A	76HB8080A51A	77HB8080A51A
	High	18x9.0	Front	28	6.1	71HB8090A61A	71HP8090A61A	75HB8090A61A	76HB8090A61A	77HB8090A61A
	High	18x9.5	Front	50	6.6	71HB8095A66A	71HP8095A66A	75HB8095A66A	76HB8095A66A	77HB8095A66A
	Low	18x10	Rear only	31	6.7	71LB8100A67A	71LP8100A67A	75LB8100A67A	76LB8100A67A	77LB8100A67A
	Low	18x11.0	Rear only	43	7.7	71LB8110A77A	71LP8110A77A	75LB8110A77A	76LB8110A77A	77LB8110A77A

20"	High	20x7.0	Front	6	4.25	71HB0070A43A	71HP0070A43A	75HB0070A43A	76HB0070A43A	77HB0070A43A
	High	20x8.0	Front	19	5.25	71HB0080A53A	71HP0080A53A	75HB0080A53A	76HB0080A53A	77HB0080A53A
	High	20x9.0	Front	32	6.25	71HB0090A63A	71HP0090A63A	75HB0090A63A	76HB0090A63A	77HB0090A63A
	Low	20x10.5	Rear only	43	7.5	71LB0105A75A	71LP0105A75A	75LB0105A75A	76LB0105A75A	77LB0105A75A
	Low	20x11.0	Rear only	50	8	71LB0110A80A	71LP0110A80A	75LB0110A80A	76LB0110A80A	77LB0110A80A

Mustang GT500 (S197) 2013+

5x4.5 (A) bolt circle
Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
17"	Low	17x9.5	Rear only	42	7.00	71LB7095A70A	71LP7095A70A	75LB7095A70A	76LB7095A70A	77LB7095A70A
	Low	17x10.0	Rear only	48	7.50	71LB7100A75A	71LP7100A75A	75LB7100A75A	76LB7100A75A	77LB7100A75A
	Low	17x10.5	Rear only	42	7.50	71LB7105A75A	71LP7105A75A	75LB7105A75A	76LB7105A75A	77LB7105A75A

18"	High	18x5.0	Front	-23	2.10	71HB8050A21A*	71HP8050A21A*	75HB8050A21A*	76HB8050A21A*	77HB8050A21A*
	Low	18x10.0	Rear only	56	7.70	71LB8100A77A	71LP8100A77A	75LB8100A77A	76LB8100A77A	77LB8100A77A
	Low	18x10.5	Rear only	50	7.70	71LB8105A77A	71LP8105A77A	75LB8105A77A	76LB8105A77A	77LB8105A77A

* Denotes: Front side of caliper on the outer piston will contact the back of the wheel spoke. Wheel spacer is required

20"	High	20x7.0	Front	6	4.25	71HB0070A43A	71HP0070A43A	75HB0070A43A	76HB0070A43A	77HB0070A43A
	High	20x8.0	Frnt/Rear	19	5.25	71HB0080A53A	71HP0080A53A	75HB0080A53A	76HB0080A53A	77HB0080A53A
	High	20x9.0	Frnt/Rear	32	6.25	71HB0090A63A	71HP0090A63A	75HB0090A63A	76HB0090A63A	77HB0090A63A
	High	20x10.0	Frnt/Rear	43	7.25	71HB0100A73A	71HP0100A73A	75HB0100A73A	76HB0100A73A	77HB0100A73A
	High	20x10.5	Rear only	50	7.75	71HB0105A78A	71HP0105A78A	75HB0105A78A	76HB0105A78A	77HB0105A78A

Mustang GT500 (S197) 2006-2012

Brembo front brakes - 14" rotor, 5x4.5 (A) bolt circle
15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Medium	15x9	Rear only	37	6.50	71MB-509A65A^	71MP-509A65A^	75MB-509A65A^	76MB-509A65A^	77MB-509A65A^
	Medium	15x10	Rear only	50	7.50	71MB-510A75A^	71MP-510A75A^	75MB-510A75A^	76MB-510A75A^	77MB-510A75A^

^ Denotes: Steeda or BMR Rear Sway bar Relocation Brackets required

17"	High	17x5.0	Front	-21	2.20	71HB7050A22A	71HP7050A22A	75HB7050A22A	76HB7050A22A	77HB7050A22A
	High	17x7.0	Front	5	4.20	71HB7070A42A	71HP7070A42A	75HB7070A42A	76HB7070A42A	77HB7070A42A
	High	17x8.0	Frnt/Rear	18	5.20	71HB7080A52A	71HP7080A52A	75HB7080A52A	76HB7080A52A	77HB7080A52A
	High	17x9.5	Frnt/Rear	37	6.70	71HB7095A67A	71HP7095A67A	75HB7095A67A	76HB7095A67A	77HB7095A67A
	Medium	17x10.0	Rear only	59	7.80	71MB7100A78A	71MP7100A78A	75MB7100A78A	76MB7100A78A	77MB7100A78A

18"	High	18x5.0	Front	-23	2.10	71HB8050A21A	71HP8050A21A	75HB8050A21A	76HB8050A21A	77HB8050A21A
	High	18x7.0	Front	3	4.10	71HB8070A41A	71HP8070A41A	75HB8070A41A	76HB8070A41A	77HB8070A41A
	High	18x8.0	Frnt/Rear	15	5.10	71HB8080A51A	71HP8080A51A	75HB8080A51A	76HB8080A51A	77HB8080A51A
	High	18x10.0	Frnt/Rear	41	7.10	71HB8100A71A	71HP8100A71A	75HB8100A71A	76HB8100A71A	77HB8100A71A
	Medium	18x10.0	Rear only	56	7.70	71MB8100A77A	71MP8100A77A	75MB8100A77A	76MB8100A77A	77MB8100A77A

20"	High	20x7.0	Front	6	4.25	71HB0070A43A	71HP0070A43A	75HB0070A43A	76HB0070A43A	77HB0070A43A
	High	20x8.0	Frnt/Rear	19	5.25	71HB0080A53A	71HP0080A53A	75HB0080A53A	76HB0080A53A	77HB0080A53A
	High	20x9.0	Frnt/Rear	32	6.25	71HB0090A63A	71HP0090A63A	75HB0090A63A	76HB0090A63A	77HB0090A63A
	High	20x10.0	Frnt/Rear	44	7.25	71HB0100A73A	71HP0100A73A	75HB0100A73A	76HB0100A73A	77HB0100A73A

Mustang GT (S197) 2011-2014

Brembo brakes - 14" front rotor, 5x4.5 (A) bolt circle

15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Medium	15x9	Rear only	37	6.50	71MB-509A65A^	71MP-509A65A^	75MB-509A65A^	76MB-509A65A^	77MB-509A65A^
	Medium	15x10	Rear only	50	7.50	71MB-510A75A^	71MP-510A75A^	75MB-510A75A^	76MB-510A75A^	77MB-510A75A^
	Medium	15x10	Rear only	50	7.50	71MB-510A75SB^	71MP-510A75SB^	75MB-510A75SB^	76MB-510A75SB^	77MB-510A75SB^

^ Denotes: Steeda or BMR Rear Sway bar Relocation Brackets required

Part number ending in "SB" denotes Single outside beadlock with black anodized beadlock ring

17"	High	17x5.0	Front	-21	2.20	71HB7050A22A	71HP7050A22A	75HB7050A22A	76HB7050A22A	77HB7050A22A
	High	17x7.0	Front	5	4.20	71HB7070A42A	71HP7070A42A	75HB7070A42A	76HB7070A42A	77HB7070A42A
	High	17x8.0	Frnt/Rear	18	5.20	71HB7080A52A	71HP7080A52A	75HB7080A52A	76HB7080A52A	77HB7080A52A
	High	17x9.5	Frnt/Rear	37	6.70	71HB7095A67A	71HP7095A67A	75HB7095A67A	76HB7095A67A	77HB7095A67A
	Medium	17x10.0	Rear only	59	7.80	71MB7100A78A	71MP7100A78A	75MB7100A78A	76MB7100A78A	77MB7100A78A

18"	High	18x5.0	Front	-23	2.10	71HB8050A21A	71HP8050A21A	75HB8050A21A	76HB8050A21A	77HB8050A21A
	High	18x7.0	Front	3	4.10	71HB8070A41A	71HP8070A41A	75HB8070A41A	76HB8070A41A	77HB8070A41A
	High	18x8.0	Frnt/Rear	15	5.10	71HB8080A51A	71HP8080A51A	75HB8080A51A	76HB8080A51A	77HB8080A51A
	High	18x10.0	Frnt/Rear	41	7.10	71HB8100A71A	71HP8100A71A	75HB8100A71A	76HB8100A71A	77HB8100A71A
	Medium	18x10.0	Rear only	56	7.70	71MB8100A77A	71MP8100A77A	75MB8100A77A	76MB8100A77A	77MB8100A77A

20"	High	20x7.0	Front	6	4.25	71HB0070A43A	71HP0070A43A	75HB0070A43A	76HB0070A43A	77HB0070A43A
	High	20x8.0	Frnt/Rear	19	5.25	71HB0080A53A	71HP0080A53A	75HB0080A53A	76HB0080A53A	77HB0080A53A
	High	20x9.0	Frnt/Rear	32	6.25	71HB0090A63A	71HP0090A63A	75HB0090A63A	76HB0090A63A	77HB0090A63A
	High	20x10.0	Frnt/Rear	44	7.25	71HB0100A73A	71HP0100A73A	75HB0100A73A	76HB0100A73A	77HB0100A73A

Mustang GT (S197) 2011-2014

Standard Ford brakes - 13" front rotor 5x4.5 (A) bolt circle. A'Star/Magnum/& V-Series 17x4.5 front will also fit. 15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Medium	15x9	Rear only	37	6.50	71MB-509A65A^	71MP-509A65A^	75MB-509A65A^	76MB-509A65A^	77MB-509A65A^
	Medium	15x10	Rear only	50	7.50	71MB-510A75A^	71MP-510A75A^	75MB-510A75A^	76MB-510A75A^	77MB-510A75A^

^ Denotes: Steeda or BMR Rear Sway bar Relocation Brackets required

17"	Low	17x5.0	Front	-3	2.90	71LB7050A30A	71LP7050A30A	75LB7050A30A	76LB7050A30A	77LB7050A30A
	Low	17x7.0	Front	10	4.40	71LB7070A45A	71LP7070A45A	75LB7070A45A	76LB7070A45A	77LB7070A45A
	Low	17x8.0	Frnt/Rear	23	5.40	71LB7080A55A	71LP7080A55A	75LB7080A55A	76LB7080A55A	77LB7080A55A
	Low	17x9.5	Frnt/Rear	42	6.90	71LB7095A70A	71LP7095A70A	75LB7095A70A	76LB7095A70A	77LB7095A70A
	Low	17x10.0	Rear only	48	7.40	71LB7100A75A	71LP7100A75A	75LB7100A75A	76LB7100A75A	77LB7100A75A
	Low	17x10.5	Rear only	55	7.90	71LB7105A80A^	71LP7105A80A^	75LB7105A80A^	76LB7105A80A^	77LB7105A80A^

^ Denotes: edgy fit/watch tire width/Test wheel on car before mounting tire

18"	Low	18x5.0	Front	-8	2.70	71LB8050A27A	71LP8050A27A	75LB8050A27A	76LB8050A27A	77LB8050A27A
	Low	18x7.0	Front	18	4.70	71LB8070A47A	71LP8070A47A	75LB8070A47A	76LB8070A47A	77LB8070A47A
	Low	18x8.0	Frnt/Rear	30	5.70	71LB8080A57A	71LP8080A57A	75LB8080A57A	76LB8080A57A	77LB8080A57A
	Low	18x9.0	Frnt/Rear	44	6.70	71LB8090A67A	71LP8090A67A	75LB8090A67A	76LB8090A67A	77LB8090A67A
	Low	18x10.0	Rear only	43	7.20	71LB8100A72A^	71LP8100A72A^	75LB8100A72A^	76LB8100A72A^	77LB8100A72A^
	Low	18x10.5	Rear only	50	7.70	71LB8105A77A^	71LP8105A77A^	75LB8105A77A^	76LB8105A77A^	77LB8105A77A^

^ Denotes: edgy fit/watch tire width/Test wheel on car before mounting tire

20"	Low	20x7.0	Front	13	4.50	71LB0070A45A	71LP0070A45A	75LB0070A45A	76LB0070A45A	77LB0070A45A
	Low	20x8.0	Frnt/Rear	25	5.50	71LB0080A55A	71LP0080A55A	75LB0080A55A	76LB0080A55A	77LB0080A55A
	Low	20x9.0	Frnt/Rear	39	6.50	71LB0090A65A	71LP0090A65A	75LB0090A65A	76LB0090A65A	77LB0090A65A
	Low	20x9.5	Frnt/Rear	45	7.00	71LB0095A70A	71LP0095A70A	75LB0095A70A	76LB0095A70A	77LB0095A70A
	Low	20x10.0	Rear only	51	7.50	71LB0100A75A	71LP0100A75A	75LB0100A75A	76LB0100A75A	77LB0100A75A
	Low	20x10.5	Rear only	58	8.00	71LB0105A80A	71LP0105A80A	75LB0105A80A	76LB0105A80A	77LB0105A80A

Mustang GT (S197) 2005-2010

Also Mustang GT 2011+ Base 5x4.5 (A) bolt circle 12.44" front rotor.

15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable.

A'Star/Magnum/& V-Series 17x4.5 front will also fit. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Medium	15x4	Front	-27	1.50	71MB-504A15A	71MP-504A15A	75MB-504A15A	76MB-504A15A	77MB-504A15A
	Medium	15x8	Rear only	25	5.50	71MB-508A55A	71MP-508A55A	75MB-508A55A	76MB-508A55A	77MB-508A55A
	Medium	15x9	Rear only	37	6.50	71MB-509A65A^	71MP-509A65A^	75MB-509A65A^	76MB-509A65A^	77MB-509A65A^
	Medium	15x10	Rear only	50	7.50	71MB-510A75A^	71MP-510A75A^	75MB-510A75A^	76MB-510A75A^	77MB-510A75A^

A 15" front wheel wider than 4" requires a 17" or 18" diameter wheel

^ Denotes: Steeda or BMR Rear Sway bar Relocation Brackets required

17"	Medium	17x4.7	Front	1	2.90	71MB7047A29A	71MP7047A29A	75MB7047A29A	76MB7047A29A	77MB7047A29A
	Medium	17x7.0	Front	20	4.80	71MB7070A48A	71MP7070A48A	75MB7070A48A	76MB7070A48A	77MB7070A48A
	Medium	17x8.0	Frnt/Rear	33	5.80	71MB7080A58A	71MP7080A58A	75MB7080A58A	76MB7080A58A	77MB7080A58A
	Medium	17x9.5	Frnt/Rear	40	6.80	71MB7095A68A	71MP7095A68A	75MB7095A68A	76MB7095A68A	77MB7095A68A
	Medium	17x10.0	Rear only	58	7.80	71MB7100A78A	71MP7100A78A	75MB7100A78A	76MB7100A78A	77MB7100A78A
	Medium	17x10.5	Rear only	53	7.80	71MB7105A78A^	71MP7105A78A^	75MB7105A78A^	76MB7105A78A^	77MB7105A78A^

^ Denotes: edgy fit/watch tire width/Test wheel on car before mounting tire

18"	Medium	18x5.0	Front	6	3.20	71MB8050A32A	71MP8050A32A	75MB8050A32A	76MB8050A32A	77MB8050A32A
	Medium	18x7.0	Front	18	4.70	71MB8070A47A	71MP8070A47A	75MB8070A47A	76MB8070A47A	77MB8070A47A
	Medium	18x8.0	Frnt/Rear	30	5.70	71MB8080A57A	71MP8080A57A	75MB8080A57A	76MB8080A57A	77MB8080A57A
	Medium	18x9.5	Frnt/Rear	37	6.70	71MB8095A67A^	71MP8095A67A^	75MB8095A67A^	76MB8095A67A^	77MB8095A67A^
	Medium	18x10.0	Rear only	56	7.70	71MB8100A77A	71MP8100A77A	75MB8100A77A	76MB8100A77A	77MB8100A77A
	Medium	18x10.5	Rear only	50	7.70	71MB8105A77A	71MP8105A77A	75MB8105A77A	76MB8105A77A	77MB8105A77A

^ Denotes: edgy fit/watch tire width/Test wheel on car before mounting tire

20"	Medium	20x7.0	Front	10	4.40	71MB0070A44A	71MP0070A44A	75MB0070A44A	76MB0070A44A	77MB0070A44A
	Medium	20x8.0	Frnt/Rear	23	5.40	71MB0080A54A	71MP0080A54A	75MB0080A54A	76MB0080A54A	77MB0080A54A
	Medium	20x9.5	Frnt/Rear	42	6.90	71MB0095A69A^	71MP0095A69A^	75MB0095A69A^	76MB0095A69A^	77MB0095A69A^
	Medium	20x10.0	Rear only	48	7.40	71MB0100A74A	71MP0100A74A	75MB0100A74A	76MB0100A74A	77MB0100A74A
	Medium	20x11.0	Rear only	61	8.40	71MB0110A84A	71MP0110A84A	75MB0110A84A	76MB0110A84A	77MB0110A84A

^ Denotes: edgy fit/watch tire width/Test wheel on car before mounting tire

Mustang Base (S197) 2005-2010 2011+ Base-use 2005-10 GT App

5x4.5 (A) bolt circle 11" front rotor 2005-2010.

15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable. AStar/Magnum/& V-Series 17x4.5 front will also fit. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Medium	15x4	Front	-27	1.50	71MB-504A15A	71MP-504A15A	75MB-504A15A	76MB-504A15A	77MB-504A15A
	Medium	15x8	Rear only	25	5.50	71MB-508A55A	71MP-508A55A	75MB-508A55A	76MB-508A55A	77MB-508A55A
	Medium	15x9	Rear only	37	6.50	71MB-509A65A^	71MP-509A65A^	75MB-509A65A^	76MB-509A65A^	77MB-509A65A^
	Medium	15x10	Rear only	50	7.50	71MB-510A75A^	71MP-510A75A^	75MB-510A75A^	76MB-510A75A^	77MB-510A75A^

A 15" front wheel wider than 4" requires a 17" or 18" diameter wheel

^ Denotes: Steeda or BMR Rear Sway bar Relocation Brackets required

17"	Medium	17x4.7	Front	1	2.90	71MB7047A29A	71MP7047A29A	75MB7047A29A	76MB7047A29A	77MB7047A29A
	Medium	17x7.0	Front	20	4.80	71MB7070A48A	71MP7070A48A	75MB7070A48A	76MB7070A48A	77MB7070A48A
	Medium	17x8.0	Frnt/Rear	33	5.80	71MB7080A58A	71MP7080A58A	75MB7080A58A	76MB7080A58A	77MB7080A58A
	Medium	17x9.0	Frnt/Rear	46	6.80	71MB7090A68A	71MP7090A68A	75MB7090A68A	76MB7090A68A	77MB7090A68A
	Medium	17x9.5	Frnt/Rear	40	6.80	71MB7095A68A	71MP7095A68A	75MB7095A68A	76MB7095A68A	77MB7095A68A
	Medium	17x10.0	Rear only	58	7.80	71MB7100A78A	71MP7100A78A	75MB7100A78A	76MB7100A78A	77MB7100A78A
	Medium	17x10.5	Rear only	53	7.80	71MB7105A78A^	71MP7105A78A^	75MB7105A78A^	76MB7105A78A^	77MB7105A78A^

^ Denotes: edgy fit/watch tire width/Test wheel on car before mounting tire

18"	Medium	18x5.0	Front	6	3.20	71MB8050A32A	71MP8050A32A	75MB8050A32A	76MB8050A32A	77MB8050A32A
	Medium	18x7.0	Front	18	4.70	71MB8070A47A	71MP8070A47A	75MB8070A47A	76MB8070A47A	77MB8070A47A
	Medium	18x8.0	Frnt/Rear	30	5.70	71MB8080A57A	71MP8080A57A	75MB8080A57A	76MB8080A57A	77MB8080A57A
	Medium	18x9.0	Frnt/Rear	44	6.70	71MB8090A67A	71MP8090A67A	75MB8090A67A	76MB8090A67A	77MB8090A67A
	Medium	18x9.5	Frnt/Rear	37	6.70	71MB8095A67A^	71MP8095A67A^	75MB8095A67A^	76MB8095A67A^	77MB8095A67A^
	Medium	18x10.0	Rear only	56	7.70	71MB8100A77A	71MP8100A77A	75MB8100A77A	76MB8100A77A	77MB8100A77A
	Medium	18x10.5	Rear only	50	7.70	71MB8105A77A	71MP8105A77A	75MB8105A77A	76MB8105A77A	77MB8105A77A

^ Denotes: edgy fit/watch tire width/Test wheel on car before mounting tire

20"	Medium	20x7.0	Front	10	4.40	71MB0070A44A	71MP0070A44A	75MB0070A44A	76MB0070A44A	77MB0070A44A
	Medium	20x8.0	Frnt/Rear	23	5.40	71MB0080A54A	71MP0080A54A	75MB0080A54A	76MB0080A54A	77MB0080A54A
	Medium	20x9.5	Frnt/Rear	42	6.90	71MB0095A69A^	71MP0095A69A^	75MB0095A69A^	76MB0095A69A^	77MB0095A69A^
	Medium	20x10.0	Rear only	48	7.40	71MB0100A74A	71MP0100A74A	75MB0100A74A	76MB0100A74A	77MB0100A74A
	Medium	20x10.5	Rear only	55	7.90	71MB0105A79A	71MP0105A79A	75MB0105A79A	76MB0105A79A	77MB0105A79A

^ Denotes: edgy fit/watch tire width/Test wheel on car before mounting tire

Mustang Cobra/Bullet/Mach1 1994-2004 (SN95)

5x4.5 (A) bolt circle - 13" front rotor. 15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable.

AStar/Magnum& V-Series 17x4.5 front will also fit. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Medium	15x8	Rear only	25	5.50	71MB-508A55A	71MP-508A55A	75MB-508A55A	76MB-508A55A	77MB-508A55A
	Medium	15x9	Rear only	13	5.50	71MB-509A55A	71MP-509A55A	75MB-509A55A	76MB-509A55A	77MB-509A55A
	Medium	15x10.33	Rear only	21	6.50	71MB-510A65A**	71MP-510A65A**	75MB-510A65A**	76MB-510A65A**	77MB-510A65A**

** Denotes that 1/2 wheel spacer is required with longer wheel studs plus caliper banjo fitting nut will need to be reduced to half its current size & fitting itself rounded on corner closest to the wheel. Stock rear outer tie rod will need to be replaced with aftermarket. Other mods may be required & will vary per car. Trial fit wheel before mounting tire.

17"	Medium	17x4.5	Front	-14	2.20	71MB7045A22A	71MP7045A22A	75MB7045A22A	76MB7045A22A	77MB7045A22A
	Medium	17x7.0	Front	20	4.80	71MB7070A48A	71MP7070A48A	75MB7070A48A	76MB7070A48A	77MB7070A48A
	Medium	17x8.0	Frnt/Rear	33	5.80	71MB7080A58A	71MP7080A58A	75MB7080A58A	76MB7080A58A	77MB7080A58A
	Medium	17x9.0	Rear only	20	5.80	71MB7090A58A	71MP7090A58A	75MB7090A58A	76MB7090A58A	77MB7090A58A
	Medium	17x10.0	Rear only	21	6.30	71MB7100A63A^	71MP7100A63A^	75MB7100A63A^	76MB7100A63A^	77MB7100A63A^

^ Denotes: edgy fit/watch tire width/Test wheel on car before mounting tire

18"	Medium	18x5.0	Front	6	3.20	71MB8050A32A	71MP8050A32A	75MB8050A32A	76MB8050A32A	77MB8050A32A
	Medium	18x7.0	Front	5	4.20	71MB8070A42A	71MP8070A42A	75MB8070A42A	76MB8070A42A	77MB8070A42A
	Medium	18x8.0	Frnt/Rear	18	5.20	71MB8080A52A	71MP8080A52A	75MB8080A52A	76MB8080A52A	77MB8080A52A
	Medium	18x9.0	Frnt/Rear	25	5.70	71MB8090A57A	71MP8090A57A	75MB8090A57A	76MB8090A57A	77MB8090A57A
	Medium	18x10.0	Rear only	18	6.20	71MB8100A62A^	71MP8100A62A^	75MB8100A62A^	76MB8100A62A^	77MB8100A62A^

^ Denotes: edgy fit/watch tire width/Test wheel on car before mounting tire

20"	Medium	20x7.0	Front	10	4.40	71MB0070A44A	71MP0070A44A	75MB0070A44A	76MB0070A44A	77MB0070A44A
	Medium	20x8.0	Frt/Rear	23	5.40	71MB0080A54A	71MP0080A54A	75MB0080A54A	76MB0080A54A	77MB0080A54A
	Medium	20x9.0	Frt/Rear	30	5.90	71MB0090A59A	71MP0090A59A	75MB0090A59A	76MB0090A59A	77MB0090A59A
	Medium	20x9.5	Rear only	29	6.40	71MB0095A64A	71MP0095A64A	75MB0095A64A	76MB0095A64A	77MB0095A64A
	Medium	20x10.0	Rear only	23	6.40	71MB0100A64A^	71MP0100A64A^	75MB0100A64A^	76MB0100A64A^	77MB0100A64A^

^ Denotes: edgy fit/watch tire width/Test wheel on car before mounting tire

Mustang (SN95) GT & Base 1994-2004

5x4.5 (A) bolt circle

15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Medium	15x4	Front	-26	1.50	71MB-504A15A	71MP-504A15A	75MB-504A15A	76MB-504A15A	77MB-504A15A
	Medium	15x5.33	Front	-16	2.50	71MB-505A25A	71MP-505A25A	75MB-505A25A	76MB-505A25A	77MB-505A25A
	Medium	15x6.33	Front	-3	3.50	71MB-506A35A	71MP-506A35A	75MB-506A35A	76MB-506A35A	77MB-506A35A
	Medium	15x7.33	Front	10	4.50	71MB-507A45A	71MP-507A45A	75MB-507A45A	76MB-507A45A	77MB-507A45A
	Medium	15x8	Frt/Rear	25	5.50	71MB-508A55A	71MP-508A55A	75MB-508A55A	76MB-508A55A	77MB-508A55A
	Medium	15x9	Rear only	25	6.50	71MB-509A65A	71MP-509A65A	75MB-509A65A	76MB-509A65A	77MB-509A65A
	Medium	15x10.33	Rear only	21	6.50	71MB-510A65A^	71MP-510A65A^	75MB-510A65A^	76MB-510A65A^	77MB-510A65A^

^ Denotes: edgy fit/watch tire width/Test wheel on car before mounting tire

17"	Medium	17x4.5	Front	-14	2.20	71MB7045A22A	71MP7045A22A	75MB7045A22A	76MB7045A22A	77MB7045A22A
	Medium	17x7.0	Front	20	4.80	71MB7070A48A	71MP7070A48A	75MB7070A48A	76MB7070A48A	77MB7070A48A
	Medium	17x8.0	Frt/Rear	33	5.80	71MB7080A58A	71MP7080A58A	75MB7080A58A	76MB7080A58A	77MB7080A58A
	Medium	17x9.0	Rear only	20	5.80	71MB7090A58A	71MP7090A58A	75MB7090A58A	76MB7090A58A	77MB7090A58A
	Medium	17x10.0	Rear only	21	6.30	71MB7100A63A^	71MP7100A63A^	75MB7100A63A^	76MB7100A63A^	77MB7100A63A^

^ Denotes: edgy fit/watch tire width/Test wheel on car before mounting tire

18"	Medium	18x5.0	Front	6	3.20	71MB8050A32A	71MP8050A32A	75MB8050A32A	76MB8050A32A	77MB8050A32A
	Medium	18x7.0	Front	5	4.20	71MB8070A42A	71MP8070A42A	75MB8070A42A	76MB8070A42A	77MB8070A42A
	Medium	18x8.0	Frt/Rear	18	5.20	71MB8080A52A	71MP8080A52A	75MB8080A52A	76MB8080A52A	77MB8080A52A
	Medium	18x9.0	Frt/Rear	25	5.70	71MB8090A57A	71MP8090A57A	75MB8090A57A	76MB8090A57A	77MB8090A57A
	Medium	18x10.0	Rear only	18	6.20	71MB8100A62A^	71MP8100A62A^	75MB8100A62A^	76MB8100A62A^	77MB8100A62A^

^ Denotes: edgy fit/watch tire width/Test wheel on car before mounting tire

20"	Medium	20x7.0	Front	10	4.40	71MB0070A44A	71MP0070A44A	75MB0070A44A	76MB0070A44A	77MB0070A44A
	Medium	20x8.0	Frt/Rear	23	5.40	71MB0080A54A	71MP0080A54A	75MB0080A54A	76MB0080A54A	77MB0080A54A
	Medium	20x9.0	Frt/Rear	30	5.90	71MB0090A59A	71MP0090A59A	75MB0090A59A	76MB0090A59A	77MB0090A59A
	Medium	20x10.0	Rear only	23	6.40	71MB0100A64A^	71MP0100A64A^	75MB0100A64A^	76MB0100A64A^	77MB0100A64A^

^ Denotes: edgy fit/watch tire width/Test wheel on car before mounting tire

Mustang Fox Cobra R 1993

5x4.5 (A) bolt circle

15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Medium	15X8	Rear only	25	5.50	71MB-508A55A	71MP-508A55A	75MB-508A55A	76MB-508A55A	77MB-508A55A
	Medium	15X9	Rear only	25	6.50	71MB-509A65A*	71MP-509A65A*	75MB-509A65A*	76MB-509A65A*	77MB-509A65A*

* Denotes exhaust modification and removal of quad shocks are required

17"	Medium	17x4.5	Front	-14	2.20	71MB7045A22A	71MP7045A22A	75MB7045A22A	76MB7045A22A	77MB7045A22A
	Medium	17x7.0	Front	20	4.80	71MB7070A48A	71MP7070A48A	75MB7070A48A	76MB7070A48A	77MB7070A48A
	Medium	17x8.0	Frnt/Rear	33	5.80	71MB7080A58A	71MP7080A58A	75MB7080A58A	76MB7080A58A	77MB7080A58A
	Medium	17x8.5	Frnt/Rear	27	5.80	71MB7085A58A	71MP7085A58A	75MB7085A58A	76MB7085A58A	77MB7085A58A

18"	Medium	18x5.0	Front	6	3.20	71MB8050A32A	71MP8050A32A	75MB8050A32A	76MB8050A32A	77MB8050A32A
	Medium	18x7.0	Front	5	4.20	71MB8070A42A	71MP8070A42A	75MB8070A42A	76MB8070A42A	77MB8070A42A
	Medium	18x8.0	Frnt/Rear	18	5.20	71MB8080A52A	71MP8080A52A	75MB8080A52A	76MB8080A52A	77MB8080A52A
	Medium	18x9.0	Frnt/Rear	25	5.70	71MB8090A57A	71MP8090A57A	75MB8090A57A	76MB8090A57A	77MB8090A57A
	Medium	18x9.5	Rear only	24	6.20	71MB8095A62A	71MP8095A62A	75MB8095A62A	76MB8095A62A	77MB8095A62A

20"	Medium	20x7.0	Front	10	4.40	71MB0070A44A	71MP0070A44A	75MB0070A44A	76MB0070A44A	77MB0070A44A
	Medium	20x8.0	Frnt/Rear	23	5.40	71MB0080A54A	71MP0080A54A	75MB0080A54A	76MB0080A54A	77MB0080A54A
	Medium	20x9.0	Frnt/Rear	30	5.90	71MB0085A59A	71MP0085A59A	75MB0085A59A	76MB0085A59A	77MB0085A59A
	Medium	20x9.5	Rear only	29	6.40	71MB0090A64A	71MP0090A64A	75MB0090A64A	76MB0090A64A	77MB0090A64A

Mustang FOX Base/GT/LX/Cobra Pace Car & Capri 1979-1993

4x4.25 (P) bolt circle. Conical Lugs required

1/2"-RH20 Studs

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Low	15x4	Front	0	2.50	71LB-504P25C	71LP-504P25C	N/A	N/A	N/A
	Low	15x5	Front	13	2.50	71LB-505P35C	71LP-505P35C	N/A	N/A	N/A
	Low	15x6.33	Front	-4	3.50	71LB-506P35C	71LP-506P35C	N/A	N/A	N/A
	Low	15x7.33	Front	9	4.50	71LB-507P45C	71LP-507P45C	N/A	N/A	N/A
	Low	15x8.33	Rear only	21	5.50	71LB-508P55C	71LP-508P55C	N/A	N/A	N/A
	Low	15x9.33	Rear only	34	6.50	71LB-509P65C*	71LP-509P65C*	N/A	N/A	N/A
	Low	15x10.33	Rear only	21	6.50	71LB-510P65C*	71LP-510P65C*	N/A	N/A	N/A

* Denotes removal of quad shocks, exhaust modifications, and roll fenders

Mustang FOX Base/GT/LX/Cobra Pace Car & Capri 1979-1993

5x4.5 (A) bolt circle

15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Low	15x4	Front		2.50	71LB-504A25A	71LP-504A25A	75LB-504A25A	76LB-504A25A	77LB-504A25A
	Low	15x5	Front	13	3.50	71LB-505A35A	71LP-505A35A	75LB-505A35A	76LB-505A35A	77LB-505A35A
	Low	15x6.33	Front	-4	3.50	71LB-506A35A	71LP-506A35A	75LB-506A35A	76LB-506A35A	77LB-506A35A
	Low	15x7.33	Front	9	4.50	71LB-507A35A	71LP-507A35A	75LB-507A35A	76LB-507A35A	77LB-507A35A
	Low	15x8.33	Rear only	21	5.50	71LB-508A55A	71LP-508A55A	75LB-508A55A	76LB-508A55A	77LB-508A55A
	Low	15x9.33	Rear only	34	6.50	71LB-509A65A*	71LP-509A65A*	75LB-509A65A*	76LB-509A65A*	77LB-509A65A*
	Low	15x10.33	Rear only	21	6.50	71LB-510A65A*	71LP-510A65A*	75LB-510A65A*	76LB-510A65A*	77LB-510A65A*

* Denotes removal of quad shocks, exhaust modifications, and roll fenders

17"	Low	17x4.5	Front	-27	1.70	71LB7045A17A	71LP7045A17A	75LB7045A17A	76LB7045A17A	77LB7045A17A
	Low	17x7.0	Front	10	4.40	71LB7070A45A	71LP7070A45A	75LB7070A45A	76LB7070A45A	77LB7070A45A
	Low	17x8.0	Frnt/Rear	23	5.40	71LB7080A55A	71LP7080A55A	75LB7080A55A	76LB7080A55A	77LB7080A55A
	Low	17x9.0	Frnt/Rear	23	5.90	71LB7090A60A*	71LP7090A60A*	75LB7090A60A*	76LB7090A60A*	77LB7090A60A*

* Denotes removal of quad shocks and exhaust modifications

18"	Low	18x5.0	Front	-8	2.70	71LB8050A27A	71LP8050A27A	75LB8050A27A	76LB8050A27A	77LB8050A27A
	Low	18x7.0	Front	5	4.20	71LB8070A42A	71LP8070A42A	75LB8070A42A	76LB8070A42A	77LB8070A42A
	Low	18x8.0	Frnt/Rear	18	5.20	71LB8080A52A	71LP8080A52A	75LB8080A52A	76LB8080A52A	77LB8080A52A
	Low	18x9.0	Rear only	30	6.20	71LB8090A62A*	71LP8090A62A*	75LB8090A62A*	76LB8090A62A*	77LB8090A62A*

* Denotes removal of quad shocks and exhaust modifications

20"	Low	20x7.0	Front	0	4.00	71LB0070A40A	71LP0070A40A	75LB0070A40A	76LB0070A40A	77LB0070A40A
	Low	20x8.0	Frnt/Rear	38	5.00	71LB0080A50A	71LP0080A50A	75LB0080A50A	76LB0080A50A	77LB0080A50A
	Low	20x9.0	Rear only	25	6.00	71LB0090A60A*	71LP0090A60A*	75LB0090A60A*	76LB0090A60A*	77LB0090A60A*

* Denotes removal of quad shocks and exhaust modifications

Mustang Fox/SVO 1984-1986

Only 5 lug Fox body, 5x4.5 (A) bolt circle

15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable. Conical Lugs req'd 17"/18"/20".

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Medium	15x4	Front	-26	1.50	71MB-504A15A	71MP-504A15A	75MB-504A15A	76MB-504A15A	77MB-504A15A
	Medium	15x5.33	Front	-16	2.50	71MB-505A25A	71MP-505A25A	75MB-505A25A	76MB-505A25A	77MB-505A25A
	Medium	15x6.33	Front	-3	3.50	71MB-506A35A	71MP-506A35A	75MB-506A35A	76MB-506A35A	77MB-506A35A
	Medium	15x7.33	Front	10	4.50	71MB-507A45A	71MP-507A45A	75MB-507A45A	76MB-507A45A	77MB-507A45A
	Medium	15x8	Frnt/Rear	26	5.50	71MB-508A55A	71MP-508A55A	75MB-508A55A	76MB-508A55A	77MB-508A55A
	Medium	15x9	Rear only	37	6.50	71MB-509A65A	71MP-509A65A	75MB-509A65A	76MB-509A65A	77MB-509A65A

17"	Medium	17x4.5	Front	-14	2.20	71MB7045A22A	71MP7045A22A	75MB7045A22A	76MB7045A22A	77MB7045A22A
	Medium	17x6.0	Front	8	3.80	71MB7070A38A	71MP7070A38A	75MB7070A38A	76MB7070A38A	77MB7070A38A
	Medium	17x7.0	Front	20	4.80	71MB7070A48A	71MP7070A48A	75MB7070A48A	76MB7070A48A	77MB7070A48A
	Medium	17x8.0	Frnt/Rear	34	5.80	71MB7080A58A	71MP7080A58A	75MB7080A58A	76MB7080A58A	77MB7080A58A
	Medium	17x9.0	Rear only	46	6.30	71MB7090A63A	71MP7090A63A	75MB7090A63A	76MB7090A63A	77MB7090A63A

18"	Medium	18x5.0	Front	-8	2.70	71MB8050A27A	71MP8050A27A	75MB8050A27A	76MB8050A27A	77MB8050A27A
	Medium	18x7.0	Front	18	4.70	71MB8070A47A	71MP8070A47A	75MB8070A47A	76MB8070A47A	77MB8070A47A
	Medium	18x8.0	Frnt/Rear	30	5.70	71MB8080A57A	71MP8080A57A	75MB8080A57A	76MB8080A57A	77MB8080A57A
	Medium	18x9.0	Rear only	30	6.20	71MB8090A62A*	71MP8090A62A*	75MB8090A62A*	76MB8090A62A*	77MB8090A62A*

* Denotes removal of quad shocks and exhaust modifications

20"	Medium	20x7.0	Front	23	4.90	71MB0070A49A	71MP0070A49A	75MB0070A49A	76MB0070A49A	77MB0070A49A
	Medium	20x8.0	Frnt/Rear	36	5.90	71MB0080A59A	71MP0080A59A	75MB0080A59A	76MB0080A59A	77MB0080A59A
	Medium	20x9.0	Rear only	36	6.40	71MB0090A64A*	71MP0090A64A*	75MB0090A64A*	76MB0090A64A*	77MB0090A64A*

* Denotes removal of quad shocks and exhaust modifications

Mustang (All) 1968-1973

5x4.5 (A) bolt circle

15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Low	15x4	Front	-2	2.50	71LB-504A25A	71LP-504A25A	75LB-504A25A	76LB-504A25A	77LB-504A25A
	Low	15x5.33	Front	10	3.50	71LB-505A35A	71LP-505A35A	75LB-505A35A	76LB-505A35A	77LB-505A35A
	Low	15x6.33	Front	-3	3.50	71LB-506A35A	71LP-506A35A	75LB-506A35A	76LB-506A35A	77LB-506A35A
	Low	15x7.33	Front	10	4.50	71LB-507A45A	71LP-507A45A	75LB-507A45A	76LB-507A45A	77LB-507A45A
	Low	15x8.33	Frnt/Rear	-1	4.50	71LB-508A45A	71LP-508A45A	75LB-508A45A	76LB-508A45A	77LB-508A45A
	Low	15x9.33	Rear only	12	5.50	71LB-509A55A^	71LP-509A55A^	75LB-509A55A^	76LB-509A55A^	77LB-509A55A^

^ Denotes the need to relocate rear stabilizer bar, if equipped. Except on the Boss 429

17"	Low	17x4.5	Front	-27	1.70	71LB7045A17A	71LP7045A17A	75LB7045A17A	76LB7045A17A	77LB7045A17A
	Low	17x7.0	Front	-3	3.90	71LB7070A40A	71LP7070A40A	75LB7070A40A	76LB7070A40A	77LB7070A40A
	Low	17x8.0	Frnt/Rear	10	4.90	71LB7080A50A	71LP7080A50A	75LB7080A50A	76LB7080A50A	77LB7080A50A
	Low	17x9.0	Rear only	10	5.40	71LB7090A55A^	71LP7090A55A^	75LB7090A55A^	76LB7090A55A^	77LB7090A55A^

^ Denotes the need to relocate rear stabilizer bar, if equipped. Except on the Boss 429

18"	Low	18x5.0	Front	-20	2.20	71LB8050A22A	71LP8050A22A	75LB8050A22A	76LB8050A22A	77LB8050A22A
	Low	18x7.0	Front	-8	3.70	71LB8070A37A	71LP8070A37A	75LB8070A37A	76LB8070A37A	77LB8070A37A
	Low	18x8.0	Frnt/Rear	5	4.70	71LB8080A47A	71LP8080A47A	75LB8080A47A	76LB8080A47A	77LB8080A47A
	Low	18x9.0	Rear only	5	5.20	71LB8090A52A^	71LP8090A52A^	75LB8090A52A^	76LB8090A52A^	77LB8090A52A^

^ Denotes the need to relocate rear stabilizer bar, if equipped. Except on the Boss 429

Mustang (All) 1967-1968

5x4.5 (A) bolt circle

15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Low	15x4	Front	0	2.50	71LB-504A25A	71LP-504A25A	75LB-504A25A	76LB-504A25A	77LB-504A25A
	Low	15x5.33	Front	-17	2.50	71LB-505A25A	71LP-505A25A	75LB-505A25A	76LB-505A25A	77LB-505A25A
	Low	15x6.33	Front	-4	3.50	71LB-506A35A	71LP-506A35A	75LB-506A35A	76LB-506A35A	77LB-506A35A
	Low	15X7.33	Frnt/Rear	9	4.50	71LB-507A45A	71LP-507A45A	75LB-507A45A	76LB-507A45A	77LB-507A45A
	Low	15X8.33	Rear only	21	5.50	71LB-508A55A	71LP-508A55A	75LB-508A55A	76LB-508A55A	77LB-508A55A

17"	Low	17x4.5	Front	-27	1.70	71LB7045A17A	71LP7045A17A	75LB7045A17A	76LB7045A17A	77LB7045A17A
	Low	17x7.0	Front	10	4.40	71LB7070A45A	71LP7070A45A	75LB7070A45A	76LB7070A45A	77LB7070A45A
	Low	17x8.0	Frnt/Rear	10	4.90	71LB7080A50A	71LP7080A50A	75LB7080A50A	76LB7080A50A	77LB7080A50A
	Low	17x9.0	Rear only	10	5.40	71LB7090A55A	71LP7090A55A	75LB7090A55A	76LB7090A55A	77LB7090A55A

18"	Low	18X5.0	Front	-20	2.20	71LB8050A22A	71LP8050A22A	75LB8050A22A	76LB8050A22A	77LB8050A22A
	Low	18X7.0	Front	-8	3.70	71LB8070A37A	71LP8070A37A	75LB8070A37A	76LB8070A37A	77LB8070A37A
	Low	18x8.0	Frnt/Rear	5	4.70	71LB8080A47A	71LP8080A47A	75LB8080A47A	76LB8080A47A	77LB8080A47A
	Low	18x9.0	Rear only	5	5.20	71LB8090A52A*	71LP8090A52A*	75LB8090A52A*	76LB8090A52A*	77LB8090A52A*

* Denotes the need to relocate rear stabilizer bar, if equipped. Except on the Boss 429

Mustang (All) 1965-1966

5x4.5 (A) bolt circle

15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Low	15x4	Front	0	2.50	71LB-504A25A	71LP-504A25A	75LB-504A25A	76LB-504A25A	77LB-504A25A
	Low	15x5.33	Front	-17	2.50	71LB-505A25A	71LP-505A25A	75LB-505A25A	76LB-505A25A	77LB-505A25A
	Low	15X7.33	Frnt/Rear	9	4.50	71LB-507A45A	71LP-507A45A	75LB-507A45A	76LB-507A45A	77LB-507A45A
	Low	15X8.33	Rear only	-4	4.50	71LB-508A45A	71LP-508A45A	75LB-508A45A	76LB-508A45A	77LB-508A45A

17"	Low	17x4.5	Front	-27	1.70	71LB7045A17A	71LP7045A17A	75LB7045A17A	76LB7045A17A	77LB7045A17A
	Low	17x7.0	Frnt/Rear	10	4.40	71LB7070A45A	71LP7070A45A	75LB7070A45A	76LB7070A45A	77LB7070A45A
	Low	17x8.0	Rear only	-3	4.40	71LB7080A45A	71LP7080A45A	75LB7080A45A	76LB7080A45A	77LB7080A45A

18"	Low	18X5.0	Front	-20	2.20	71LB8050A22A	71LP8050A22A	75LB8050A22A	76LB8050A22A	77LB8050A22A
	Low	18X7.0	Front	-8	3.70	71LB8070A37A	71LP8070A37A	75LB8070A37A	76LB8070A37A	77LB8070A37A
	Low	18x8.0	Frnt/Rear	5	4.70	71LB8080A47A	71LP8080A47A	75LB8080A47A	76LB8080A47A	77LB8080A47A

Thunderbird/Base/LX/Turbo Coupe 1983-1988

5x4.5 (A) bolt circle

15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Low	15x4	Front	-2	2.50	71LB-504A25A	71LP-504A25A	75LB-504A25A	76LB-504A25A	77LB-504A25A
	Low	15x5.33	Front	10	3.50	71LB-505A35A	71LP-505A35A	75LB-505A35A	76LB-505A35A	77LB-505A35A
	Low	15x6.33	Front	-3	3.50	71LB-506A35A	71LP-506A35A	75LB-506A35A	76LB-506A35A	77LB-506A35A
	Low	15x7.33	Front	9	4.50	71LB-507A45A	71LP-507A45A	75LB-507A45A	76LB-507A45A	77LB-507A45A
	Low	15x8.33	Frnt/Rear	21	5.50	71LB-508A55A	71LP-508A55A	75LB-508A55A	76LB-508A55A	77LB-508A55A
	Low	15X9.33	Rear only	34	6.50	71LB-509A65A^	71LP-509A65A^	75LB-509A65A^	76LB-509A65A^	77LB-509A65A^

^ Denotes removal of quad shocks and exhaust modifications

17"	Low	17x4.5	Front	-27	1.70	71LB7045A17A	71LP7045A17A	75LB7045A17A	76LB7045A17A	77LB7045A17A
	Low	17x7.0	Front	10	4.40	71LB7070A45A	71LP7070A45A	75LB7070A45A	76LB7070A45A	77LB7070A45A
	Low	17x8.0	Frnt/Rear	23	5.40	71LB7080A55A	71LP7080A55A	75LB7080A55A	76LB7080A55A	77LB7080A55A
	Low	17x9.0	Rear only	23	5.90	71LB7090A60A^	71LP7090A60A^	75LB7090A60A^	76LB7090A60A^	77LB7090A60A^

^ Denotes removal of quad shocks and exhaust modifications

18"	Low	18x5.0	Front	-13	2.20	71LB8050A22A	71LP8050A22A	75LB8050A22A	76LB8050A22A	77LB8050A22A
	Low	18x7.0	Front	5	4.20	71LB8070A42A	71LP8070A42A	75LB8070A42A	76LB8070A42A	77LB8070A42A
	Low	18x8.0	Frnt/Rear	18	5.20	71LB8080A52A	71LP8080A52A	75LB8080A52A	76LB8080A52A	77LB8080A52A
	Low	18x9.0	Rear only	30	6.20	71LB8090A62A^	71LP8090A62A^	75LB8090A62A^	76LB8090A62A^	77LB8090A62A^

^ Denotes removal of quad shocks and exhaust modifications

LTD LX/Fox 1984-1985

5x4.5 (A) bolt circle

15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Low	15x4	Front	-2	2.50	71LB-504A25A	71LP-504A25A	75LB-504A25A	76LB-504A25A	77LB-504A25A
	Low	15x5.33	Front	-17	2.50	71LB-505A25A	71LP-505A25A	75LB-505A25A	76LB-505A25A	77LB-505A25A
	Low	15x6.33	Front	-3	3.50	71LB-506A35A	71LP-506A35A	75LB-506A35A	76LB-506A35A	77LB-506A35A
	Low	15X8.33	Frnt/Rear	21	5.50	71LB-508A55A	71LP-508A55A	75LB-508A55A	76LB-508A55A	77LB-508A55A
	Low	15X9.33	Rear only	34	6.50	71LB-509A65A^	71LP-509A65A^	75LB-509A65A^	76LB-509A65A^	77LB-509A65A^

^ Denotes removal of quad shocks and exhaust modifications

17"	Low	17x4.5	Front	-27	1.70	71LB7045A17A	71LP7045A17A	75LB7045A17A	76LB7045A17A	77LB7045A17A
	Low	17x7.0	Front	10	4.40	71LB7070A45A	71LP7070A45A	75LB7070A45A	76LB7070A45A	77LB7070A45A
	Low	17x8.0	Frnt/Rear	23	5.40	71LB7080A55A	71LP7080A55A	75LB7080A55A	76LB7080A55A	77LB7080A55A
	Low	17x9.0	Rear only	23	5.90	71LB7090A60A^	71LP7090A60A^	75LB7090A60A^	76LB7090A60A^	77LB7090A60A^

^ Denotes removal of quad shocks and exhaust modifications

18"	Low	18x5.0	Front	-13	2.20	71LB8050A22A	71LP8050A22A	75LB8050A22A	76LB8050A22A	77LB8050A22A
	Low	18x7.0	Front	5	4.20	71LB8070A42A	71LP8070A42A	75LB8070A42A	76LB8070A42A	77LB8070A42A
	Low	18x7.5	Front	11	4.70	71LB8075A47A	71LP8075A47A	75LB8075A47A	76LB8075A47A	77LB8075A47A
	Low	18x8.0	Frnt/Rear	18	5.20	71LB8080A52A	71LP8080A52A	75LB8080A52A	76LB8080A52A	77LB8080A52A
	Low	18x9.0	Rear only	30	6.20	71LB8090A62A^	71LP8090A62A^	75LB8090A62A^	76LB8090A62A^	77LB8090A62A^

^ Denotes removal of quad shocks and exhaust modifications

Torino/Gran Torino/Elite 1972-1976. Ranchero 1972-1979

5x4.5 (A) bolt circle

15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Low	15x4	Front	-2	2.50	71LB-504A25A	71LP-504A25A	75LB-504A25A	76LB-504A25A	77LB-504A25A
	Low	15x5.33	Front	10	3.50	71LB-505A35A	71LP-505A35A	75LB-505A35A	76LB-505A35A	77LB-505A35A
	Low	15x6.33	Front	-3	3.50	71LB-506A35A	71LP-506A35A	75LB-506A35A	76LB-506A35A	77LB-506A35A
	Low	15x7.33	Front	10	4.50	71LB-507A45A	71LP-507A45A	75LB-507A45A	76LB-507A45A	77LB-507A45A
	Low	15x8.33	Frnt/Rear	-1	4.50	71LB-508A45A	71LP-508A45A	75LB-508A45A	76LB-508A45A	77LB-508A45A
	Low	15x9.33	Rear only	12	5.50	71LB-509A55A	71LP-509A55A	75LB-509A55A	76LB-509A55A	77LB-509A55A

17"	Low	17x4.5	Front	-27	1.70	71LB7045A17A	71LP7045A17A	75LB7045A17A	76LB7045A17A	77LB7045A17A
	Low	17x7.0	Front	10	4.40	71LB7070A45A	71LP7070A45A	75LB7070A45A	76LB7070A45A	77LB7070A45A
	Low	17x8.0	Frnt/Rear	10	4.90	71LB7080A50A	71LP7080A50A	75LB7080A50A	76LB7080A50A	77LB7080A50A
	Low	17x9.0	Rear only	10	5.40	71LB7090A55A	71LP7090A55A	75LB7090A55A	76LB7090A55A	77LB7090A55A

18"	Low	18x5.0	Front	-20	2.20	71LB8050A22A	71LP8050A22A	75LB8050A22A	76LB8050A22A	77LB8050A22A
	Low	18x7.0	Front	-8	3.70	71LB8070A37A	71LP8070A37A	75LB8070A37A	76LB8070A37A	77LB8070A37A
	Low	18x8.0	Frnt/Rear	5	4.70	71LB8080A47A	71LP8080A47A	75LB8080A47A	76LB8080A47A	77LB8080A47A
	Low	18x9.0	Rear only	-8	4.70	71LB8080A47A	71LP8080A47A	75LB8080A47A	76LB8080A47A	77LB8080A47A
	Low	18x9.5	Rear only	-1	5.20	71LB8095A52A	71LP8095A52A	75LB8095A52A	76LB8095A52A	77LB8095A52A

20"	Low	20x7.0	Front	0	4.00	71LB0070A40A	71LP0070A40A	75LB0070A40A	76LB0070A40A	77LB0070A40A
	Low	20x8.0	Frnt/Rear	13	5.00	71LB0080A50A	71LP0080A50A	75LB0080A50A	76LB0080A50A	77LB0080A50A
	Low	20x9.0	Rear only	0	5.00	71LB0090A50A	71LP0090A50A	75LB0090A50A	76LB0090A50A	77LB0090A50A
	Low	20x9.5	Rear only	6	5.50	71LB0095A55A	71LP0095A55A	75LB0095A55A	76LB0095A55A	77LB0095A55A

Fairlane/Torino/GT/Cobra/Ranchero 1968-1971

5x4.5 (A) bolt circle

15" RT-S uses .50" long mag shank lug & 5/8 drive stud acceptable. Conical Lugs req'd 17"/18"/20"

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Low	15x4	Front	-2	2.50	71LB-504A25A	71LP-504A25A	75LB-504A25A	76LB-504A25A	77LB-504A25A
	Low	15x5.33	Front	10	3.50	71LB-505A35A	71LP-505A35A	75LB-505A35A	76LB-505A35A	77LB-505A35A
	Low	15x6.33	Front	-3	3.50	71LB-506A35A	71LP-506A35A	75LB-506A35A	76LB-506A35A	77LB-506A35A
	Low	15x7.33	Front	10	4.50	71LB-507A45A	71LP-507A45A	75LB-507A45A	76LB-507A45A	77LB-507A45A
	Low	15x8.33	Frnt/Rear	-1	4.50	71LB-508A45A	71LP-508A45A	75LB-508A45A	76LB-508A45A	77LB-508A45A
	Low	15x9.33	Rear only	12	5.50	71LB-509A55A	71LP-509A55A	75LB-509A55A	76LB-509A55A	77LB-509A55A

17"	Low	17x4.5	Front	-27	1.70	71LB7045A17A	71LP7045A17A	75LB7045A17A	76LB7045A17A	77LB7045A17A
	Low	17x7.0	Front	10	4.40	71LB7070A45A	71LP7070A45A	75LB7070A45A	76LB7070A45A	77LB7070A45A
	Low	17x8.0	Frnt/Rear	10	4.90	71LB7080A50A	71LP7080A50A	75LB7080A50A	76LB7080A50A	77LB7080A50A
	Low	17x9.0	Rear only	10	5.40	71LB7090A55A	71LP7090A55A	75LB7090A55A	76LB7090A55A	77LB7090A55A

18"	Low	18X5.0	Front	-20	2.20	71LB8050A22A	71LP8050A22A	75LB8050A22A	76LB8050A22A	77LB8050A22A
	Low	18X7.0	Front	-8	3.70	71LB8070A37A	71LP8070A37A	75LB8070A37A	76LB8070A37A	77LB8070A37A
	Low	18x8.0	Frnt/Rear	5	4.70	71LB8080A47A	71LP8080A47A	75LB8080A47A	76LB8080A47A	77LB8080A47A
	Low	18x9.0	Rear only	5	5.20	71LB8090A52A*	71LP8090A52A*	75LB8090A52A*	76LB8090A52A*	77LB8090A52A*

* Denotes the need to relocate rear stabilizer bar, if equipped. Except on the Boss 429

Fairlane/Torino/Ranchero 1966-1967

5x4.5 (A) bolt circle

	Pad Height	Wheel Size	Vehicle Location	Weld Offset	Back Space	S71 Black Ctr Part Number	S71 All Polished Part Number	S75 Black Ctr Part Number	S76 Black Ctr Part Number	S77 Black Ctr Part Number
15"	Low	15x4	Front	-2	2.50	71LB-504A25A	71LP-504A25A	75LB-504A25A	76LB-504A25A	77LB-504A25A
	Low	15x5.33	Front	10	3.50	71LB-505A35A	71LP-505A35A	75LB-505A35A	76LB-505A35A	77LB-505A35A
	Low	15X7.33	Frnt/Rear	15	3.50	71LB-507A35A	71LP-507A35A	75LB-507A35A	76LB-507A35A	77LB-507A35A
	Low	15X8.33	Rear only	-5	4.50	71LB-508A45A	71LP-508A45A	75LB-508A45A	76LB-508A45A	77LB-508A45A

17"	Low	17x4.5	Front	-27	1.70	71LB7045A17A	71LP7045A17A	75LB7045A17A	76LB7045A17A	77LB7045A17A
	Low	17x7.0	Frnt/Rear	11	4.40	71LB7070A45A	71LP7070A45A	75LB7070A45A	76LB7070A45A	77LB7070A45A
	Low	17x8.0	Rear only	11	4.90	71LB7080A50A	71LP7080A50A	75LB7080A50A	76LB7080A50A	77LB7080A50A

18"	Low	18x5.0	Front	-20	2.20	71LB8050A22A	71LP8050A22A	75LB8050A22A	76LB8050A22A	77LB8050A22A
	Low	18x7.0	Frnt/Rear	10	3.70	71LB8070A37A	71LP8070A37A	75LB8070A37A	76LB8070A37A	77LB8070A37A
	Low	18x8.0	Rear only	3	4.70	71LB8080A47A	71LP8080A47A	75LB8080A47A	76LB8080A47A	77LB8080A47A

This fitment guide applies to vehicles with O.E. suspension/wheel wells/and brakes unless otherwise noted.

Other sizes and offsets are available/please call the Sales and Tech Department for more information