

# RTS Application Guide

## TOYOTA SUPRA -TURBO

This fitment guide applies to vehicles with O.E. suspension, wheel wells, and brakes unless otherwise noted.

### 1993-1998 Supra Turbo

5x4.5 (A) bolt circle

15" RT-S - Short mag shank lug. Conical Lugs req'd - 17"/18"/20".

	Pad Height	Size	Vehicle Location	Off-set	Back Space	S71 All Polished Part Number	S71 Black Center Part Number	S75 Black Center Part Number	S76 Black Center Part Number	S77 Black Center Part Number
15"	Medium	15x9	Rear Only	37	6.50	71MP-509A65A	71MB-509A65A	75MB-509A65A	76MB-509A65A	77MB-509A65A
	Medium	15x10	Rear Only	50	7.50	71MP-510A75A	71MB-510A75A	75MB-510A75A	76MB-510A75A	77MB-510A75A
	Low	15x11.33	Rear Only	34	7.50	71LP-511A75A~	71LB-511A75A~	75LB-511A75A~	76LB-511A75A~	77LB-511A75A~

~TRD wide body kit required

17"	High	17x5.0	Front	-20	2.20	71HP7050A22A	71HB7050A22A	75HB7050A22A	76HB7050A22A	77HB7050A22A
	Medium	17x5.0	Front	8	3.30	71MP7050A33A*	71MB7050A33A*	75MB7050A33A*	76MB7050A33A*	77MB7050A33A*
	High	17x8.0	Front	18	5.20	71HP7080A52A	71HB7080A52A	75HB7080A52A	76HB7080A52A	77HB7080A52A
	Medium	17x8.0	Front	45	6.30	71MP7080A63A*	71MB7080A63A*	75MB7080A63A*	76MB7080A63A*	77MB7080A63A*
	High	17x9.0	Front	30	6.20	71HP7090A62A	71HB7090A62A	75HB7090A62A	76HB7090A62A	77HB7090A62A
	Medium	17x9.0	Front	58	7.30	71MP7090A73A*	71MB7090A73A*	75MB7090A73A*	76MB7090A73A*	77MB7090A73A*
	Medium	17x10.0	Rear Only	58	7.80	71MP7100A78A	71MB7100A78A	75MB7100A78A	76MB7100A78A	77MB7100A78A
	Medium	17x10.5	Rear Only	52	7.80	71MP7105A78A	71MB7105A78A	75MB7105A78A	76MB7105A78A	77MB7105A78A

\*Alternative fitment to "tuck" the wheel more into the wheel well. A .500" (13mm) spacer will be required to clear brake caliper.

High pad height front wheel fitments will not require a wheel spacer, but the fender lip will need to be rolled.

18"	High	18x5.0	Front	-23	2.10	71HP8050A21A	71HB8050A21A	75HB8050A21A	76HB8050A21A	77HB8050A21A
	Medium	18x5.0	Front	5	3.20	71MP8050A32A*	71MB8050A32A*	75MB8050A32A*	76MB8050A32A*	77MB8050A32A*
	High	18x9.0	Front	28	6.10	71HP8090A61A	71HB8090A61A	75HB8090A61A	76HB8090A61A	77HB8090A61A
	Medium	18x9.0	Front	56	7.20	71MP8090A72A*	71MB8090A72A*	75MB8090A72A*	76MB8090A72A*	77MB8090A72A*
	High	18x10.0	Front	41	7.10	71HP8100A71A	71HB8100A71A	75HB8100A71A	76HB8100A71A	77HB8100A71A
	Medium	18x10.0	Front	69	8.20	71MP8100A82A*	71MB8100A82A*	75MB8100A82A*	76MB8100A82A*	77MB8100A82A*
	Medium	18x10.0	Rear Only	56	7.70	71MP8100A77A	71MB8100A77A	75MB8100A77A	76MB8100A77A	77MB8100A77A
	Medium	18x10.5	Rear Only	50	7.70	71MP8105A77A	71MB8105A77A	75MB8105A77A	76MB8105A77A	77MB8105A77A

\*Alternative fitment to "tuck" the wheel more into the wheel well. A .500" (13mm) spacer will be required to clear brake caliper.

High pad height front wheel fitments will not require a wheel spacer, but the fender lip will need to be rolled.

20"	High	20x7.0	Front	8	4.30	71HP0070A43A	71HB0070A43A	75HB0070A43A	76HB0070A43A	77HB0070A43A
	High	20x8.5	Front	24	5.70	71HP0085A57A	71HB0085A57A	75HB0085A57A	76HB0085A57A	77HB0085A57A
	Medium	20x9.0	Rear only	48	6.90	71MP0090A69A	71MB0090A69A	75MB0090A69A	76MB0090A69A	77MB0090A69A
	Medium	20x9.5	Rear only	55	7.40	71MP0095A74A	71MB0095A74A	75MB0095A74A	76MB0095A74A	77MB0095A74A
	Medium	20x10.0	Rear only	61	7.90	71MP0100A79A	71MB0100A79A	75MB0100A79A	76MB0100A79A	77MB0100A79A

High pad height front wheel fitments do not require a wheel spacer, but the fender lip will need to be rolled.

Medium Pad alternative fitments are not available in 20" that will "tuck" the wheel more into the wheel well.

# HONDA S2000

This fitment guide applies to vehicles with O.E. suspension, wheel wells, and brakes unless otherwise noted.

## 1999-2009 S2000

5x4.5 (A) bolt circle. Conical Lugs req'd - 17"/18"/20". 15" Rear wheel fitments: Medium Pad will clear brakes, but there is not a wheel available at this time with enough positive offset to keep the wheel in the qtr

	Pad Height	Size	Vehicle Location	Off-set	B/S	S71 All Polished Part Number	S71 Black Center Part Number	S75 Black Center Part Number	S76 Black Center Part Number	S77 Black Center Part Number
17"	Medium	17x5.0	Front	8	3.30	71MP7050A33A	71MB7050A33A	75MB7050A33A	76MB7050A33A	77MB7050A33A
	Medium	17x7.0	Front	33	5.30	71MP7070A53A	71MB7070A53A	75MB7070A53A	76MB7070A53A	77MB7070A53A
	Medium	17x8.0	Front	46	6.30	71MP7080A63A	71MB7080A63A	75MB7080A63A	76MB7080A63A	77MB7080A63A
	Medium	17x9.0	Rear Only	58	7.30	71MP7090A73A	71MB7090A73A	75MB7090A73A	76MB7090A73A	77MB7090A73A
	Medium	17x9.5	Rear Only	65	7.80	71MP7095A78A	71MB7095A78A	75MB7095A78A	76MB7095A78A	77MB7095A78A
	Medium	17x10.0	Rear Only	71	8.30	71MP7100A83A	71MB7100A83A	75MB7100A83A	76MB7100A83A	77MB7100A83A

Fender lip must be rolled for all wheel fitments listed

18"	Medium	18x5.0	Front	5	3.20	71MP8050A32A	71MB8050A32A	75MB8050A32A	76MB8050A32A	77MB8050A32A
	Medium	18x7.0	Front	30	5.20	71MP8070A52A	71MB8070A52A	75MB8070A52A	76MB8070A52A	77MB8070A52A
	Medium	18x8.0	Front	43	6.20	71MP8080A62A	71MB8080A62A	75MB8080A62A	76MB8080A62A	77MB8080A62A
	Medium	18x9.0	Rear Only	56	7.20	71MP8090A72A	71MB8090A72A	75MB8090A72A	76MB8090A72A	77MB8090A72A
	Medium	18x10.0	Rear Only	69	8.20	71MP8100A82A	71MB8100A82A	75MB8100A82A	76MB8100A82A	77MB8100A82A

Fender lip must be rolled for all wheel fitments listed